

Size matters – deeper cavity units with warm edge

Engineered in Switzerland

www.swisspacer.com

SWISSPACER

The edge of tomorrow.



ULTIMATE
SWISSPACER

32 mm

36 mm

Saving energy even with deeper cavity units

Insulating glass units with interior blinds and leaf-enclosing infill for domestic doors – planners, architects and specifiers are demanding increasingly larger air gaps. SWISSPACER ULTIMATE spacer bar, available in widths of 32mm and 36mm is the ideal solution – saving heating costs and increasing comfort in the home.

PERFECT APPEARANCE: 2 BECOME 1

To date, when making sealed units with large air gaps manufacturers have had to make do with the combination of two 16mm spacer bars. Why use two when one SWISSPACER in 32 or 36mm will do? It's simple to process, with an attractive finish.



SWISSPACER Psi values

Window system W/m ² K		Wood 1.4 – 1.3	PVC 1.2	Wood + Aluminium 1.4	Aluminium 1.6
Glazing		Double Triple			
Spacer bars	SWS ULTIMATE	0.031 0.029	0.032 0.030	0.032 0.030	0.036 0.031

Double glazing: 4-16-4 ($U_g = 1.1 \text{ W/m}^2\text{K}$) | Triple glazing: 4-12-4-12-4 ($U_g = 0.7 \text{ W/m}^2\text{K}$)

Source: ift Rosenheim WA-08/3 (Warm Edge working group)



Advantages and benefits of SWISSPACER ULTIMATE 32mm & 36mm

- Clean, smooth appearance
- Simple and speedy processing
- High thermal performance



Unit: mm

SWISSPACER

Vetrotech Saint-Gobain (International) AG
Zweigniederlassung Kreuzlingen
Sonnenwiesenstrasse 15
8280 Kreuzlingen, Switzerland

T +41 (0)71 686 92 70
F +41 (0)71 686 92 75
info@swisspacer.com
www.swisspacer.com

SWISSPACER

The edge of tomorrow.